

FL 9BW / 9BW LT

The FL 9BW and 9BW LT are cooled CMOS cameras designed for long-exposure imaging. They not only incorporate the high sensitivity and low noise advantages of the latest sensor technologies but also leverage Tucsen's extensive experience in cooling chamber design and advanced image processing. These cameras can capture clean and uniform images with exposure times of up to 60 minutes.



Key Features

Benefits

Scientific Grade CMOS	92% peak QE, 0.75 e ⁻ readout noise and no glow.
< 0.0005 e ⁻ /p/s Dark Current	Equivalent to the cooled CCD for long exposure imaging.
16000 : 1 Dynamic Range	More than 4X that of the CCD.
Pixel Correction Technology	High background quality ensures more accurate quantitative analysis. ^[1]
Flexible Binning Mode	Improving the sensitivity and dynamic range capability.
High Reliability Cooling Chamber	Cooled to -25°C@Room Temp. (25°C), no condensation or other problems.
Compact Design	Conducive to instrument system integration.

Typical Applications

- Chemiluminescence
- Bioluminescence
- dPCR
- Fluorescence imaging

Noted Examples

[1] The FL 9BW has excellent background uniformity, as it has basically eliminated the bad factors such as amplifier glow and bad pixels.






Figure (a) is the background image taken by FL 26BW with 600s exposure. Figure (b) is the grayscale intensity curve corresponding to the yellow region, showing excellent background uniformity.

Quantum Efficiency



Dimensions (Unit: mm)



Specifications

Product Name	FL 9BW		FL 9BW LT	
Sensor Type	BSI CMOS			
Sensor Model	SONY IMX533CLK-D			
Chrome	Mono			
Array Diagonal	15.96 mm (1")			
Effective area	11.28 mm x 11.28 mm			
Pixel Size	3.76 μm × 3.76 μm			
Resolution	3000 × 3000, 9 MP			
Peak QE	92%@540 nm			
Dark Current	< 0.0005 e-/p/s			
Gain Mode	Gain 0 HFWC	Gain 1 Balance	Gain 2 High Sensitivity 1	Gain 3 High Sensitivity 2
Full Well Capacity	48 Ke-@bin 1	16 Ke-@bin 1	7.8 Ke-@bin 1	3.1 Ke-@bin 1
Readout Mode	Standard, Low-Noise			
Readout Noise (LowNoise)	2.5 e-@Gain 0	1.0 e-@Gain 1	0.85 e-@Gain 2	0.7 e-@Gain 3
Frame Rate	19 fps@Standard Mode, 12 fps@Low Noise Mode			
Shutter Mode	Rolling			
Exposure Time	15 μs~60 min			
Image Correction	DPC			
ROI	Support			
Binning	2 x 2, 3 x 3, 4 x 4, 6 x 6, 8 x 8, 12 x 12, 16 x 16, 24 x 24			
Cooling Method	Air Cooling			
Cooling Temp.	-25°C@Room Temp. (25°C)		Locked at 0°C	
Trigger Mode	Hardware, Software			
Trigger Output	Exposure Start, Global, Readout End, High, Low			
Trigger Interface	Hirose-6-pin			
SDK	C / C++ / C# / Python			
Data Interface	USB 3.0			
Software	Mosaic V3, Sample Pro, LabVIEW, MATLAB, Micro-Manager 2.0			
Optical Interface	C-Mount / Customizable			
Bit Depth	14 bit, 16 bit			
Power Supply	12 V / 6 A			
Power Cons.	≤ 46 W			
Dimensions	76 mm (H) x 76 mm (W) x 98.5 mm (L)			
Weight	835 g			
Operating System	Windows, Linux			
Environment	Working: Temp. 0°C~40°C, HUM 10%~85% Storage: Temp. -10°C~60°C, HUM 0%~85%			

*Specifications in this manual are subject to changes without prior notice.



Follow us

+86 (591) 2805 5076 ext.818

www.tucsen.com

support@tucsen.com